

WOLF PORTRAIT SIDING PRODUCT CHECKLIST

Follow the checklist below to ensure proper list of materials needed

PRODUCT	ORDERING TIPS	NOTES
☐ Flex Flashing	Available in 6" (stocked by Wolf) and 9" (special order).	Flexible flashing used around sill pans.
☐ Nichigo G-Tape™ Flashing Tape	Available in 4" and 6".	Used around windows and doors. Apply using firm pressure.
☐ Seam Tape	Available in 2" and 3".	Use for horizontal and vertical seams. Wolf recommends 3" for cold weather installations (below 40°).
☐ BLOCK-IT* House Wrap	Available in 3', 5', 9' and 10' rolls.	BLOCK-IT* features 98% drainability. Alternates house wraps must have a 95% drainability. Failure to do so will void the Wolf Portrait Siding Limited Lifetime warranty.
☐ Wolf Portrait Siding	Silhouette Profile - Lap 7" (7 pieces/carton) Vignette Profile - Double 4" (6 pieces/carton) 1/2 square per carton.	Siding panels are 12' 6".
☐ Trim	Wolf Portrait Casing 5/4" x 4" x 20' and 5/4" x 6" x 20' Wolf Portrait Outside Corner w/J Channel 5/4" x 4" x 20' and 5/4" x 6" x 20' Wolf Portrait Inside Corner w/J Channel 5/4" x 4" x 20'	Routed out to 1.5" J channel to help accommodate for expansion and contraction caused by long runs.
☐ Starter Strip	3" x 10'	Install the starter strip along a straight and level line, nailing every 8"-12".
☐ Seam Plates	25/box Approximately 6/square Available in two profiles - Silhouette (Lap 7") and Vignette (Double 4") .	Adhesive must be applied to seam plates according to the Wolf Portrait Siding installation instructions.
☐ Adhesive	Extreme Adhesives Fast Cure for temperatures between 25°F - 35°F Extreme Adhesives White Hot for temperatures between 35°F - 100°F Coverage is roughly 7-10 seam plates/tube.	When using Extreme Adhesives Fast Cure, remember to purchase additional mixing tips as the epoxy will dry and clog mixing chambers.
☐ Nails	6D hot dipped galvanized or stainless steel nails. Not available through Wolf. Order from your local Wolf dealer.	Nail must penetrate 1" into stud.
☐ Color-Match Accessories	See Wolf Portrait Siding installation guide for the following color-match charts: DAP, Mid America, Berger and Sherwin-Williams.	Contact your Wolf Sales Rep for more information.

WOLF PORTRAIT™ SIDING
HIGH-DENSITY CELLULAR™ TECHNOLOGY



WOLF PRO

Are you a Wolf PRO? Once certified you'll be able to offer homeowners an exclusive 5-Year Labor Warranty. Contact your Wolf Sales rep for more information.

